



ATSC

ADVANCED TELEVISION
SYSTEMS COMMITTEE

ATSC Standard: Service Announcement, with Amendment No. 1

Doc. A/332:2017
6 December 2017
Amendment No. 1 approved 26 March 2021

Advanced Television Systems Committee
1776 K Street, N.W.
Washington, D.C. 20006
202-872-9160

The Advanced Television Systems Committee, Inc., is an international, non-profit organization developing voluntary standards and recommended practices for digital television. ATSC member organizations represent the broadcast, broadcast equipment, motion picture, consumer electronics, computer, cable, satellite, and semiconductor industries. ATSC also develops digital television implementation strategies and supports educational activities on ATSC standards. ATSC was formed in 1983 by the member organizations of the Joint Committee on InterSociety Coordination (JCIC): the Electronic Industries Association (EIA), the Institute of Electrical and Electronic Engineers (IEEE), the National Association of Broadcasters (NAB), the National Cable Telecommunications Association (NCTA), and the Society of Motion Picture and Television Engineers (SMPTE). For more information visit www.atsc.org.

Note: The user's attention is called to the possibility that compliance with this standard may require use of an invention covered by patent rights. By publication of this standard, no position is taken with respect to the validity of this claim or of any patent rights in connection therewith. One or more patent holders have, however, filed a statement regarding the terms on which such patent holder(s) may be willing to grant a license under these rights to individuals or entities desiring to obtain such a license. Details may be obtained from the ATSC Secretary and the patent holder.

Implementers with feedback, comments, or potential bug reports relating to this document may contact ATSC at <https://www.atsc.org/feedback/>.

Revision History

Version	Date
Candidate Standard approved	24 November 2015
Revised Candidate Standard approved	21 September 2016
A/332:2017 Standard approved	16 March 2017
Reference [13] updated to point to the published version of A/341:2017	22 May 2017
A/332:2017 Revision approved	6 December 2017
Amendment No. 1 approved	26 March 2021
Note that reference document RFC 6330, which was marked for deletion in Amendment No. 1, is preserved because of a normative reference to it in Section 5.5.1.	

Table of Contents

1. SCOPE	1
1.1 Organization	1
2. REFERENCES	1
2.1 Normative References	1
3. DEFINITION OF TERMS	2
3.1 Compliance Notation	2
3.2 Treatment of Syntactic Elements	3
3.2.1 Reserved Elements	3
3.3 Acronyms and Abbreviation	3
3.4 Terms	4
4. SYSTEM OVERVIEW	4
5. SERVICE ANNOUNCEMENT: SERVICE GUIDE	4
5.1 Introduction	4
5.2 ATSC SG Data Model	5
5.2.1 Overview	5
5.2.2 ATSC 3.0 Service Guide Data Model	5
5.2.2.1 Service Fragment	6
5.2.2.1.1 Service Type	7
5.2.2.1.2 Genre	7
5.2.2.1.3 Name and Description Elements Extensions	7
5.2.2.1.4 Content Advisory Ratings Information	9
5.2.2.1.5 Non-RRT Content Advisory Rating	11
5.2.2.1.6 Service-Level Private Extensions	12
5.2.2.2 Schedule Fragment	13
5.2.2.3 Content Fragment	13
5.2.2.3.1 Name and Description Elements Extensions	15
5.2.2.3.2 Content-Level Private Extensions	17
5.2.2.3.3 Device Capabilities	21
5.3 Description of Code Points	26
5.3.1 Capability Codes 0x0500, 0x0501, 0x580, 0x581: AVC Video	27
5.3.2 Capability Codes 0x0507, 0x0508, 0x0587, and 0x0588: 3D Video	27
5.3.3 Capability Codes 0x0509 and 0x0589: ATSC 3.0 HEVC Video	27
5.3.4 Capability Codes 0x050A and 0x058A: ATSC 3.0 HDR Video	27
5.3.5 Capability Codes 0x050F and 0x058F: 4K Resolution	27
5.3.6 Capability Codes 0x0510 and 0x0590: ATSC 3.0 HDR Video with ST2094-10 SEI	27
5.3.7 Capability Codes 0x0511 and 0x0591: ATSC 3.0 SDR Video with SL-HDR1 SEI	27
5.3.8 Capability Code 0x0200: AL-FEC	28
5.3.9 Capability Codes 0x0512 and 0x0592: ATSC 3.0 SHVC Video	28
5.3.10 Capability Codes 0x0513 and 0x0593: HFR with One Temporal Sub-Layer	28
5.3.11 Capability Codes 0x0514 and 0x0594: HFR with Unfiltered Temporal Sub-Layers	28
5.3.12 Capability Codes 0x0515 and 0x0595: HFR, Temporal Filtering	28
5.3.13 Capability Codes 0x0516 and 0x0596: ATSC 3.0 Fixed/Mobile 3D HEVC	28

5.3.14	Capability Codes 0x0517 and 0x0597: ATSC 3.0 Fixed/Mobile 3D SHVC	28
5.3.15	Capability Codes 0x0518 and 0x0598: ATSC 3.0 Wide Color Gamut	29
5.3.16	Capability Codes 0x0519 and 0x0599: ATSC 3.0 HD Progressive Video	29
5.3.17	Capability Codes 0x051A and 0x059A: Personalization Selection	29
5.3.18	Capability Codes 0x051B and 0x059B: Dialog Enhancement	29
5.3.19	Capability Codes 0x051C and 0x059C: Video Descriptive Service	29
5.3.20	Capability Codes 0x051D and 0x059D: ATSC 3.0 SD Progressive Video	29
5.3.21	Capability Category “Other” (0x08xx)	29
5.3.21.1	Capability Code 0x0800: DRM	29
5.3.21.2	Capability Code 0x0801: Companion Device	29
5.3.22	Capability Category String Codes (ubyte)	30
5.3.22.1	ubyte 0x00: Minimum HTTP Cache Size	30
5.3.23	ubyte 0x01: Minimum Broadcast Cache Size	30
5.4	SG Data Encapsulation	30
5.5	SG Delivery	31
5.5.1	SG delivery over Broadcast	31
5.5.2	SG delivery over Broadband	31
5.6	SG Data Update and Management	31
ANNEX A SCHEMA		32

Index of Tables

Table 5.1 Service Fragment	6
Table 5.2 Speech Phonetic Information Extensions in Service Fragment.....	7
Table 5.3 Content Advisory Rating Information	10
Table 5.4 Non-RRT Content Advisory Rating Information	11
Table 5.5 Service Level Private Extensions	12
Table 5.6 Schedule Fragment	13
Table 5.7 Content Fragment	14
Table 5.8 Speech Phonetic Information Extensions in Content Fragment.....	15
Table 5.9 Content-Level Private Extensions	17
Table 5.10 Device Capabilities Related Content-Level Private Extensions.....	22
Table 5.11 Capability Codes.....	23
Table 5.12 Capability Categories and Registries	26

ATSC Standard: Service Announcement (A/332)

1. SCOPE

The normative portions of this document define a standard for announcement of services in an ATSC 3.0 broadcast.

1.1 Organization

This document is organized as follows:

- Section 1 – Outlines the scope of this document and provides a general introduction.
- Section 2 – Lists references and applicable documents.
- Section 3 – Provides a definition of terms, acronyms, and abbreviations for this document.
- Section 4 – System Overview: Service Announcement and Personalization
- Section 5 – Service Announcement: Service Guide
- Annex A – Schema

2. REFERENCES

All referenced documents are subject to revision. Users of this Standard are cautioned that newer editions might or might not be compatible.

2.1 Normative References

The following documents, in whole or in part, as referenced in this document, contain specific provisions that are to be followed strictly in order to implement a provision of this Standard.

- [1] ATSC: “ATSC-Mobile DTV Standard, Part 4 – Announcement,” Doc. A/153 Part 4:2009, Advanced Television Systems Committee, Washington, D.C., 15 October 2009.
- [2] ATSC: “ATSC Standard: Signaling, Delivery, Synchronization, and Error Protection,” Doc. A/331:2021, Advanced Television Systems Committee, Washington, D.C., 19 January 2021.
- [3] IEEE: “Use of the International Systems of Units (SI): The Modern Metric System,” Doc. IEEE/ASTM SI 10, Institute of Electrical and Electronics Engineers, New York, N.Y., 2002.
- [4] IETF: “Hypertext Transfer Protocol – HTTP/1.1: Semantics and Content,” RFC 7231, Internet Engineering Task Force, June 2014.
- [5] IETF: “Augmented BNF for Syntax Specifications: ABNF,” RFC 5234, Internet Engineering Task Force, January 2008.
- [6] IETF: “UTF-8, A Transformation Format for ISO 10646,” RFC 3629, Internet Engineering Task Force, November 2003.
- [7] OMA: “Service Guide for Mobile Broadcast Services,” Version 1.0.1, document OMA-TS-BCAST_Service_Guide-V1_0_1-20130109-A, Open Mobile Alliance, 9 January 2013.
- [8] OMA: “Service Guide for Mobile Broadcast Services,” Version 1.1, document OMA-TS-BCAST_Service_Guide-V1_1-20131029-A, Open Mobile Alliance, 29 October 2013.

- [9] ATSC: “ATSC Standard: Video—HEVC, with Amendment No. 1” Doc. A/341:2019, Advanced Television Systems Committee, Washington, D.C., 14 February 2019, Amendment No. 1 approved 2 March 2021.
- [10] ATSC: “ATSC Standard: AC-4 System,” Doc. A/342-2:2021, Advanced Television Systems Committee, Washington, D.C., 10 March 2021.
- [11] ATSC: “ATSC Standard: MPEG-H System,” Doc. A/342-3:2021, Advanced Television Systems Committee, Washington, D.C., 11 March 2021.
- [12] ATSC: “ATSC Standard: Non-Real-Time Content Delivery,” Doc. A/103:2014, Advanced Television Systems Committee, Washington, D.C., 25 July 2014.
- [13] ATSC: “ATSC Standard: Captions and Subtitles, with Amendment No. 1,” Doc. A/343:2018, Advanced Television Systems Committee, Washington, D.C., 10 October 2018, Amendment No. 1 approved 8 February 2021.
- [14] ATSC: “ATSC Standard: Companion Device,” Doc. A/338:2021, Advanced Television Systems Committee, Washington, D.C., 19 February 2021.
- [15] ATSC: “ATSC 3.0 Interactive Content,” Doc. A/344:2021, Advanced Television Systems Committee, Washington, D.C., 23 March 2021.
- [16] ITU-R: “Recommendation Parameter values for the HDTV standards for production and international programme exchange,” Doc. BT.709-6, International Telecommunications Union, Geneva Switzerland, June 2015.
- [17] ITU-R: “Use of large screen digital imagery Recommendations in video information systems applications,” Doc. BT.2000-0, International Telecommunications Union, Geneva Switzerland, January 2012.
- [18] ITU-R: “Image parameter values for high dynamic range television for use in production and international programme exchange,” Doc. BT.2100-2, International Telecommunications Union, Geneva Switzerland, July 2018.
- [19] ATSC: “Audio Common Elements,” Doc. A/342-1:2021, Advanced Television Systems Committee, Washington, D.C., 9 March 2021.
- [20] IETF: “RaptorQ Forward Error Correction Scheme for Object Delivery,” RFC 6330, Internet Engineering Task Force, August 2011.

3. DEFINITION OF TERMS

With respect to definition of terms, abbreviations, and units, the practice of the Institute of Electrical and Electronics Engineers (IEEE) as outlined in the Institute’s published standards [3] shall be used. Where an abbreviation is not covered by IEEE practice or industry practice differs from IEEE practice, the abbreviation in question will be described in Section 3.3 of this document.

3.1 Compliance Notation

This section defines compliance terms for use by this document:

shall – This word indicates specific provisions that are to be followed strictly (no deviation is permitted).

shall not – This phrase indicates specific provisions that are absolutely prohibited.

should – This word indicates that a certain course of action is preferred but not necessarily required.

should not – This phrase means a certain possibility or course of action is undesirable but not prohibited.

3.2 Treatment of Syntactic Elements

This document contains symbolic references to syntactic elements used in the audio, video, and transport coding subsystems. These references are typographically distinguished by the use of a different font (e.g., `restricted`), may contain the underscore character (e.g., `sequence_end_code`) and may consist of character strings that are not English words (e.g., `dynrng`).

3.2.1 Reserved Elements

One or more reserved bits, symbols, fields, or ranges of values (i.e., elements) may be present in this document. These are used primarily to enable adding new values to a syntactical structure without altering its syntax or causing a problem with backwards compatibility, but they also can be used for other reasons.

The ATSC default value for reserved bits is ‘1.’ There is no default value for other reserved elements. Use of reserved elements except as defined in ATSC Standards or by an industry standards setting body is not permitted. See individual element semantics for mandatory settings and any additional use constraints. As currently-reserved elements may be assigned values and meanings in future versions of this Standard, receiving devices built to this version are expected to ignore all values appearing in currently-reserved elements to avoid possible future failure to function as intended.

3.3 Acronyms and Abbreviation

The following acronyms and abbreviations are used within this document.

ABNF – Augmented Backus-Naur Form

AAC – Advanced Audio Coding

AMP – Application Media Player

ATSC – Advanced Television Systems Committee

DNF – Disjunctive Normal Form

DRM – Digital Rights Management

HDR – High Dynamic Range

HEVC – High Efficiency Video Coding

HTTP – HyperText Transport Protocol

IMSC1 – Internet Media Subtitles and Captions 1

MPEG – Moving Picture Experts Group

OMA – Open Mobile Alliance

OMA BCAST – Open Mobile Alliance Broadcast Mobile Services Enabler Suite

PVR – Personal Video Recorder

RMP – Receiver Media Player

ROUTE – Real-time Object delivery over Unidirectional Transport

SDR – Standard Dynamic Range

SEI – Supplemental Enhancement Information

SG – Service Guide

SGDD – Service Guide Delivery Descriptor

SGDU – Service Guide Delivery Unit
SHVC – Scalable High Efficiency Video Coding
SL-HDR – Single Layer High Dynamic Range
XML – eXtensible Markup Language

3.4 Terms

The following terms are used within this document.

reserved – Set aside for future use by a Standard.

Content fragment – Portion of Service Announcement that describes ATSC program or content item, corresponding to Content fragment in OMA BCASST Service Guide model [7], with additions and constraints as described in this document.

Schedule fragment – Portion of Service Announcement that describes presentation scheduling of content in an ATSC service, corresponding to Schedule fragment in OMA BCASST Service Guide model [7], with additions and constraints as described in this document.

Service Announcement – Service Announcement is information regarding the ATSC services and content available.

Service fragment – Portion of Service Announcement that describes ATSC service, corresponding to Service fragment in OMA BCASST Service Guide model [7], with additions and constraints as described in this document.

Service Guide – Function of presenting Service Announcement.

4. SYSTEM OVERVIEW

The normative portions of this document define a standard for announcement of services in an ATSC 3.0 broadcast. The Service Announcement Specifications define the data formats and delivery mechanisms used to announce the content and services being delivered, or scheduled for delivery, in ATSC 3.0.

5. SERVICE ANNOUNCEMENT: SERVICE GUIDE

5.1 Introduction

In general, it is assumed that ATSC 3.0 services will be delivered by broadcast channel(s) and broadband channel(s) jointly leveraging the unidirectional one-to-many broadcast paradigm (either in fixed environment and/or mobile environment) and the bi-directional unicast paradigm in a broadband environment.

The Service Announcement function enables ATSC 3.0 Service providers to describe the ATSC 3.0 Services that they make available. From a user's point of view, the Service Announcement function enables an on-screen Service Guide that can be seen as an entry point to discover ATSC 3.0 services and to select services. Service Announcement provides descriptions of the content offerings and also may provide a filtering capability based on user preferences and content properties, such as the presence or absence of captioning, interactive enhancements, video formats (3D, SD, HD, UD), audio formats (stereo, 5.1, immersive), caption formats (IMSC1 text or image), content advisory ratings, genre, accessible audio tracks, alternate languages, etc. In the case of scheduled services, Service Announcement also provides information about the date and time each offering is scheduled to be broadcast.

This specification comprises the Service Announcement data model, data delivery format, and delivery mechanisms used to announce ATSC 3.0 services and content now being delivered, scheduled for delivery, or available on-demand, over both broadcast and broadband channels. This specification also includes the mechanisms for discovery of the Service Announcement data and mechanisms to signal updates to the Service Announcement data.

5.2 ATSC SG Data Model

5.2.1 Overview

The information available through the Service Announcement provides receivers with a robust description of the available services and content.

5.2.2 ATSC 3.0 Service Guide Data Model

This Section defines a set of constraints and extensions of the data model specified in the OMA BCAST Service Guide specification, Version 1.0.1 [7].

Service guide fragments used to announce information regarding ATSC 3.0 services and content shall conform to the data model described in this standard, which extends the OMA BCAST Service Guide specification, Version 1.0.1 [7] data model (and XML schema) in following distinct ways.

- The allowed values for existing OMA BCAST Service Guide elements are modified or constrained. These changes are intended to be consistent with the OMA BCAST SG schema.
- Additional data model elements not defined in the OMA BCAST SG are introduced. These are defined within the PrivateExt elements provided for such extensions in the OMA BCAST schema.

Service Guide data that include ATSC services is a collection of XML fragments whose syntax is described by OMA BCAST SG (using the OMA BCAST XML namespace), together with additional XML elements defined by this standard (using the ATSC 3 namespace).

Note: The following conventions apply to all tables in this Section:

- Metadata items which are represented as XML elements are shown in plain text.
- Metadata items which are represented as XML attributes are shown in *italics*.
- Additions to the data model from in OMA BCAST 1.1 [8] are **highlighted in gray and bold**.
- Additions to the data model specified in OMA BCAST (and therefore making use of the ATSC 3 namespace) are **highlighted in light gray and bold**.
- Meaning of “Type” and “Category” column is defined in OMA BCAST Service Guide specification, Version 1.0.1 [7].

The XML schema definitions for the new elements described in the tables in this document can be found in the XML schema file shown in Annex A of this document. The normative XML schema document for the schemas defined in this document can be found in Annex A.

The Service Announcement shall be represented as an XML document that conforms to the definitions in the XML schema that has namespace:

tag:atsc.org,2016:XMLSchemas/ATSC3/SA/1.0/

When any of these elements appear in the service guide, their syntax shall conform to these XML schema definitions. When any of these elements appear in the service guide, their semantics shall be as defined in this section.

5.2.2.1 Service Fragment

Service fragment shall include elements as shown in Table 5.1. Use of the Service fragment of the service guide shall conform to the specifications in OMA BCASST Service Guide specification, Version 1.0.1 [7] with extensions as shown in Table 5.1.

Table 5.1 Service Fragment

Service
<i>id</i>
<i>version</i>
<i>validFrom</i>
<i>validTo</i>
<i>globalServiceID</i>
<i>weight</i>
<i>emergency</i>
ServiceType
Name
Description
AudioLanguage
<i>languageSDPtag</i>
TextLanguage
<i>languageSDPtag</i>
ContentAdvisoryRatings
OtherRatings [Table 5.4]
TargetUserProfile
Genre
BroadcastArea
PrivateExt
ATSC3ServiceExtension
Icon
<i>MIMEType</i>
<i>width</i>
<i>height</i>
<i>dataSize</i>
MajorChannelNum
MinorChannelNum
RatingRegionTables

The following constraints apply.

- The cardinality of Name is changed from 1..N to 0..N.
- The attribute *languageSDPtag* for the elements AudioLanguage and TextLanguage is changed from “required” to “optional”.

- The element `BroadcastArea` shall not contain attribute `Polarity`. If `lev_conf` exists in the Service fragment for a target area type (as specified by the `TargetArea` sub-element) other than `shape`, it carries no meaning.

The following adaptations and extensions apply.

- For use of `serviceType`, see Section 5.2.2.1.1.
- For use of `Genre`, see Section 5.2.2.1.2.
- Elements `Name` and `Description` shall be replaced with extended elements in Section 5.2.2.1.3.
- The target level of confidence is confidence level that the terminal is indeed located within the indicated `TargetArea`. If the terminal is not located within the indicated `TargetArea`, it should not present the service. When `TargetArea` is set to `shape`, the target confidence level is 67%. When `TargetArea` is not set to `shape`, the target confidence level is 100%

5.2.2.1.1 Service Type

The `serviceType` element values are extended to include two proprietary ATSC 3.0 service types:

- A `serviceType` element shall be included with value 228 to indicate that the Service fragment contains information regarding an ATSC 3.0 Linear service.
- A `serviceType` element shall be included with value 229 to indicate that the Service fragment contains information regarding an ATSC 3.0 App-based service with app-based enhancement.

5.2.2.1.2 Genre

The `Genre` element shall be instantiated to describe the genre category for a service or for content. The ‘href’ attribute value shall select a particular genre category and be set as follows:

`<classificationSchemeURI> “:” <termID>`

where

`<classificationSchemeURI>` is `http://www.atsc.org/XMLSchemas/mh/2009/1.0/genre-cs/` and `<termID>` matches a `termID` value from the classification schema in Annex B of A/153 Part 4 [1]. The `Genre` element content shall be an empty string.

5.2.2.1.3 Name and Description Elements Extensions

Elements `Name` and `Description` elements from Service fragment are extended with addition of sub-elements and attributes related to speech phonetic information, as listed in Table 5.2.

Table 5.2 Speech Phonetic Information Extensions in Service Fragment

Name	Type	Category	Cardinality	Description	Data Type
Name	E1	NM/TM	0..N	Extended Name element which includes sub-elements to indicate name and phonetic information about name. Contains the following elements: SpeechInfoURI SpeechInfo Contains following attribute: text xml:lang	

text	A	NM/TM	1	Name of the Service.	String
xml:lang	A	NM/TM	0..1	The language of the text attribute expressed with XML attribute 'xml:lang'	String
SpeechInfoURI	E2	NM/TM	0..N	The URI address where SpeechInfo object for parent Name element is acquired. Speech file may be encoded in SSML format (http://www.w3.org/TR/speech-synthesis11/) or similar types of mark-up languages. Contains following attribute: content-type content-enc	anyURI
content-type	A	NM/TM	0..1	Content-type of SpeechInfo object referenced by SpeechInfoURI.	String
content-enc	A	NM/TM	0..1	Content encoding of SpeechInfo object referenced by SpeechInfoURI.	String
SpeechInfo	E2	NM/TM	0..N	Embedded Speech information object for parent Name element. Contains following attribute: content-type content-enc	anyURI
content-type	A	NM/TM	0..1	Content-type of SpeechInfo object.	String
content-enc	A	NM/TM	0..1	Content encoding of SpeechInfo object.	String
Description	E1	NM/TM	1..N	Extended Description element which includes sub-elements to indicate description and phonetic information about description. Contains the following elements: SpeechInfoURI SpeechInfo Contains following attribute: text xml:lang	
text	A	NM/TM	1	Description of the Service.	String
xml:lang	A	NM/TM	0..1	The language of the text attribute expressed with XML attribute 'xml:lang'	String
SpeechInfoURI	E2	NM/TM	0..N	The URI address where SpeechInfo object for parent Name element is acquired. Speech file may be encoded in SSML format (http://www.w3.org/TR/speech-synthesis11/) or similar types of mark up languages. Contains following attribute: content-type content-enc	anyURI
content-type	A	NM/TM	0..1	Content-type of SpeechInfo object referenced by SpeechInfoURI.	String
content-enc	A	NM/TM	0..1	Content encoding of SpeechInfo object referenced by SpeechInfoURI.	String
SpeechInfo	E2	NM/TM	0..N	Embedded Speech information object for parent Name element. Contains following attribute: content-type content-enc	anyURI
content-type	A	NM/TM	0..1	Content-type of SpeechInfo object.	String
content-enc	A	NM/TM	0..1	Content encoding of SpeechInfo object.	String

Additionally, the following constraints apply.

- When more than one SpeechInfoURI element and SpeechInfo element are present inside a parent Name or Description element in the service guide, the value of content-type

attribute of each of the `SpeechInfoURI` element and `SpeechInfo` element shall be different.

- The semantics of `content-type` attribute for `SpeechInfoURI` element and `SpeechInfo` element shall obey the semantics of `Content-Type` header of HTTP/1.1 protocol RFC 7231 [4].
- When the `content-type` attribute is not present for `SpeechInfoURI` element or `SpeechInfo` element it is inferred to have a value of “`application/ssml+xml`” for that element.
- The semantics of `content-enc` attribute for `SpeechInfoURI` element and `SpeechInfo` element shall obey the semantics of `Content-Encoding` header of HTTP/1.1 protocol RFC 7231 [4].
- When the `content-enc` attribute is not present for `SpeechInfoURI` element or `SpeechInfo` element the associated speech information object for the corresponding `SpeechInfoURI` element or `SpeechInfo` is assumed to have no additional content encoding applied.

5.2.2.1.4 Content Advisory Ratings Information

This section describes content advisory rating information corresponding to a rating system defined by a Rating Region Table (RRT). RRT is defined in Annex of A/331 [2]. RRT `RatingRegionTables` element may be signaled in Service fragment as described in section 5.2.2.1.4. Content advisory rating not corresponding to defined RRT are described in section 5.2.2.1.5. The content advisory rating is indicated for each rating region. For each rating region, rating value is provided for one or more rating dimensions. The content advisory rating is indicated as listed in Table 5.3.

Table 5.3 Content Advisory Rating Information

Name	Type	Category	Cardinality	Description	Data Type
ContentAdvisoryRatings	E1	NM/TM	0..N	Content advisory rating - one for each rating region. Contains the following elements: RegionIdentifier RatingDescription RatedDimensions RatingDimVal	
RegionIdentifier	E2	NM/TM	0..1	Specifies the rating region for which the following rating description, rated dimensions, rating dimension, and rating value data is specified. If not present, the value of RegionIdentifier is inferred to be 1.	unsignedByte
RatingDescription	E2	NM/TM	1	Rating description text which represents the rating suitable for on-screen display. Contains the following attribute: xml:lang	string
xml:lang	A	NM/TM	0..1	The language of the RatingDescription expressed with XML attribute 'xml:lang'	string
RatedDimensions	E2	NM/TM	0..1	The number of region specific rating dimensions for which content advisory rating is specified.	unsignedByte
RatingDimVal	E2	NM/TM	1..N	Content advisory rating dimension and rating value for each rated dimension. Contains the following elements: RatingDimension RatingValueString	
RatingDimension	E3	NM/TM	0..1	Rating dimension index for which the rating value is specified.	unsignedByte
RatingValueString	E3	NM/TM	1	Rating value text string for the rating dimension specified in the associated RatingDimension element.	string

Additionally, the following constraints apply.

- The number of occurrences of the RatingDimVal element must be equal to the value inside the RatedDimensions element.
- The value of the element RatingDimension shall be less than or equal to the number of rating dimensions defined in the rating region table.
- The value of the element RatingValueString shall be equal to one of the values defined in the rating region table for the rating dimension indicated by the value of the associated RatingDimension element.
- When not present the value of RatingDimension is inferred to be equal to 0.
- When not present the value of RatedDimensions is inferred to be equal to 1.

The content advisory rating information can be indicated in service announcement at one or more of the following locations:

- Inside a Service fragment for a service
The content advisory rating information (`ContentAdvisoryRatings` element) can be indicated inside a Service fragment.
- Inside a Content fragment for a program or content
The content advisory ratings information (`ContentAdvisoryRatings` element) can be included in Content fragment instead of in Service fragment or in addition to in the Service fragment. When content advisory information is included in both the Service fragment and the Content fragment then the information in the Content fragment overrides the information in the Service fragment.

5.2.2.1.5 Non-RRT Content Advisory Rating

Content advisory rating not corresponding to defined RRT are carried as described by appropriate regional authorities using the structure described in **Table 5.4**.

Table 5.4 Non-RRT Content Advisory Rating Information

Name	Type	Category	Card- inality	Description
OtherRatings	E1	NM/TM	0..N	Content advisory rating – not corresponding to defined RRT. Contains the following attribute: <code>ratingScheme</code> Contains one of the following elements (inside XML schema choice element): <code>RatingInformationString</code> <code>RatingInformationData</code>
ratingScheme	A	NM/TM	1	Specifies the scheme URI for the rating described by <code>RatingInformationString/</code> <code>RatingInformationData</code> element
RatingInformationString	E2	NM/TM	0..1	Rating information value string corresponding to the rating scheme defined by <code>ratingScheme</code> . The interpretation of this element is specified by appropriate regional authorities.
RatingInformationData	E2	NM/TM	0..1	Container element for rating information value data corresponding to the rating scheme defined by <code>ratingScheme</code> . The interpretation of the child element(s) of this element is specified by appropriate regional authorities. Contains <code>xs:any</code> element(s).

Additionally, the following constraints apply.

- Each `OtherRatings` element inside the Service fragment shall have a unique `ratingScheme` value.
- Each `OtherRatings` element inside the Content fragment shall have a unique `ratingScheme` value.

The non-RRT content advisory rating information can be indicated in service announcement at one or more of the following locations:

- Inside a Service fragment for a service
The non-RRT content advisory rating information (`OtherRatings` element) can be indicated inside a Service fragment.

- Inside a Content fragment for a program or content
The non-RRT content advisory ratings information (`OtherRatings` element) can be included in Content fragment instead of in Service fragment or in addition to in the Service fragment. When non-RRT content advisory information is included in both the Service fragment and the Content fragment then the information in the Content fragment over-rides the information in the Service fragment.

5.2.2.1.6 Service-Level Private Extensions

Elements from the ATSC 3 namespace are used within the OMA `PrivateExt` element, to indicate ATSC 3 service related elements and attributes, as listed in Table 5.5.

Table 5.5 Service Level Private Extensions

Name	Type	Category	Card- inality	Description	Data Type
<code>ATSC3ServiceExtension</code>	E1	NM/TM	1	Additional information about ATSC 3.0 service. Contains the following elements: Icon MajorChannelNum MinorChannelNum	
<code>Icon</code>	E2	NM/TM	0..N	URL pointing to icon used to represent the service in ESG. Multiple URLs could be used to point to icons of different width and height or different representation formats. Contains the following optional attributes: MIMETYPE width height dataSize	anyURI
<code>MIMETYPE</code>	A	NM/TM	0..1	The optional MIME type of the icon allowing receivers to preemptively ignore fetching image types they are not capable of presenting.	String
<code>width</code>	A	NM/TM	0..1	Width of the referenced image in pixels	unsignedInt
<code>height</code>	A	NM/TM	0..1	Height of the referenced image in pixels	unsignedInt
<code>dataSize</code>	A	NM/TM	0..1	Size of the image data in bytes.	unsignedInt
<code>MajorChannelNum</code>	E2	NM/TM	0..1	Major channel number of the service. The language is expressed using built-in XML attribute 'xml:lang' with this element.	String
<code>MinorChannelNum</code>	E2	NM/TM	0..1	Minor channel number of the service. The language is expressed using built-in XML attribute 'xml:lang' with this element.	String
<code>RatingRegionTables</code>	E2	NM/TM	0..1	Rating Region Table. Syntax of <code>RatingRegionTables</code> shall be as specified in Annex of A/331 [2]. The contents of this element in the service announcement shall match those sent in the service signaling.	

Note: The attributes associated with the `Icon` element are optional. They can be provided as hints to allow the receiver ESG system to avoid accessing image data that it cannot process.

5.2.2.2 Schedule Fragment

Schedule fragment shall include elements as shown in Table 5.6. Use of the Schedule fragment of the service guide shall conform to the specifications in OMA BCAS**T** Service Guide specification, Version 1.0.1 [7] with extensions as specified in this section.

Table 5.6 Schedule Fragment

Schedule
<i>id</i>
<i>version</i>
<i>validFrom</i>
<i>validTo</i>
ServiceReference
<i>idRef</i>
ContentReference
<i>idRef</i>
<i>contentLocation</i>
PresentationWindow
<i>startTime</i>
<i>endTime</i>
<i>duration</i>
<i>id</i>
TermsOfUse
PrivateExt

The following constraints apply.

- The attributes `defaultSchedule`, `onDemand`, of the element `Schedule` shall not be present.
- The elements `InteractivityDataReference`, `AutoStart`, `DistributionWindow`, `PreviewDataReference` shall not be present. When an element is not present all its sub-elements and attributes are also not present.
- The sub-element `PreviewDataIDRef` of the element `TermsofUse` shall not be present.

5.2.2.3 Content Fragment

Content fragment shall include elements as shown in Table 5.7. Use of the Content fragment of the service guide shall conform to the specifications in OMA BCAS**T** Service Guide specification, Version 1.0.1 [7] and for elements **highlighted in gray and bold** to the specifications of OMA BCAS**T** Service Guide specification, Version 1. 1 [8] with additional extensions as shown in Table 5.7.

Table 5.7 Content Fragment

Content
<i>id</i>
<i>version</i>
<i>validFrom</i>
<i>validTo</i>
<i>globalContentID</i>
<i>baseCID</i>
ServiceReference
<i>idRef</i>
<i>weight</i>
Name
Description
AudioLanguage
<i>languageSDPTag</i>
TextLanguage
<i>languageSDPTag</i>
Length
ContentAdvisoryRatings [Table 5.3]
OtherRatings [Table 5.4]
TargetUserProfile
Genre
BroadcastArea
TermsOfUse
Popularity
<i>rating</i>
<i>noOfViews</i>
<i>noOfDiscussions</i>
<i>samplingDate</i>
Freshness
<i>releasDate</i>
<i>broadcastDate</i>
PrivateExt
Components
AudioComponent
<i>language</i>
VideoComponent
<i>language</i>
CCComponent
<i>language</i>
AppComponent
<i>language</i>
Capabilities
ContentIcon
MIMEType
<i>width</i>
<i>height</i>

dataSize
Preview
usage
PreviewIcon
MIMETYPE
width
height
dataSize
Description
PreviewContent
MIMETYPE
width
height
dataSize

The following constraints apply.

- The elements of `startTime` and `endTime` shall not be present.
- The sub-element `PreviewDataIDRef` of the element `TermsOfUse` shall not be present.
- The attribute `languageSDPTag` for the elements `AudioLanguage` and `TextLanguage` is changed from “required” to “optional”.
- The element `BroadcastArea` shall not contain attribute `polarity`. If `lev_conf` exists in the Content fragment for a target area type (as specified by the `TargetArea` sub-element) other than `shape`, it carries no meaning.

The following adaptations and extensions apply.

- Elements `Name` and `Description` shall be replaced with extended elements in Section 5.2.2.3.1.
- For use of `genre`, see Section 5.2.2.1.2.
- The target level of confidence is confidence level that the terminal is indeed located within the indicated `TargetArea`. If the terminal is not located within the indicated `TargetArea`, it should not present the service. When `TargetArea` is set to `shape`, the target confidence level is 67%. When `TargetArea` is not set to `shape`, the target confidence level is 100%

5.2.2.3.1 Name and Description Elements Extensions

Elements `Name` and `Description` elements from Content fragment are extended with addition of sub-elements and attributes related to speech phonetic information, as listed in Table 5.8.

Table 5.8 Speech Phonetic Information Extensions in Content Fragment

Name	Type	Category	Cardinality	Description	Data Type
Name	E1	NM/TM	0..N	Extended Name element which includes sub-elements to indicate name and phonetic information about name. Contains the following elements: <code>SpeechInfoURI</code> <code>SpeechInfo</code> Contains the following attribute: <code>text</code>	

				xml:lang	
text	A	NM/TM	1	Name of the 'Content' fragment.	String
xml:lang	A	NM/TM	0..1	The language of the text attribute expressed with XML attribute 'xml:lang'	String
SpeechInfoURI	E2	NM/TM	0..N	The URI address where SpeechInfo object for parent Name element is acquired. Speech file may be encoded in SSML format (http://www.w3.org/TR/speech-synthesis11/) or similar types of mark-up languages. Contains following attribute: content-type content-enc	anyURI
Content-type	A	NM/TM	0..1	Content-type of SpeechInfo object referenced by SpeechInfoURI.	String
Content-enc	A	NM/TM	0..1	Content encoding of SpeechInfo object referenced by SpeechInfoURI.	String
SpeechInfo	E2	NM/TM	0..N	Embedded Speech information object for parent Name element. Contains following attribute: content-type content-enc	anyURI
Content-type	A	NM/TM	0..1	Content-type of SpeechInfo object.	String
Content-enc	A	NM/TM	0..1	Content encoding of SpeechInfo object.	String
Description	E1	NM/TM	1..N	Extended Description element which includes sub-elements to indicate description and phonetic information about description. Contains the following elements: SpeechInfoURI SpeechInfo Contains following attribute: text xml:lang	
text	A	NM/TM	1	Description of the Content	String
xml:lang	A	NM/TM	0..1	The language of the text attribute expressed with XML attribute 'xml:lang'	String
SpeechInfoURI	E2	NM/TM	0..N	The URI address where SpeechInfo object for parent Description element is acquired. Speech file may be encoded in SSML format (http://www.w3.org/TR/speech-synthesis11/) or similar types of mark-up languages. Contains following attribute: content-type content-enc	anyURI
content-type	A	NM/TM	0..1	Content-type of SpeechInfo object referenced by SpeechInfoURI.	String
content-enc	A	NM/TM	0..1	Content encoding of SpeechInfo object referenced by SpeechInfoURI.	String
SpeechInfo	E2	NM/TM	0..N	Embedded Speech information object for parent Description element. Contains following attribute: content-type content-enc	anyURI
content-type	A	NM/TM	0..1	Content-type of SpeechInfo object.	String
content-enc	A	NM/TM	0..1	Content encoding of SpeechInfo object.	String

Additionally, the following constraints apply.

- When more than one `speechInfoURI` element and `speechInfo` element are present inside a parent `Name` or `Description` element in the service guide, the value of `content-type` attribute of each of the `speechInfoURI` element and `speechInfo` element shall be different.
- The semantics of `content-type` attribute for `speechInfoURI` element and `speechInfo` element shall obey the semantics of `Content-Type` header of HTTP/1.1 protocol RFC 7231 [4].
- When the `content-type` attribute is not present for `speechInfoURI` element or `speechInfo` element it is inferred to have a value of “`application/ssml+xml`” for that element.
- The semantics of `content-enc` attribute for `speechInfoURI` element and `speechInfo` element shall obey the semantics of `Content-Encoding` header of HTTP/1.1 protocol RFC 7231 [4].
- When the `content-enc` attribute is not present for `speechInfoURI` element or `speechInfo` element the associated speech information object for the corresponding `speechInfoURI` element or `speechInfo` is assumed to have no additional content encoding applied.

5.2.2.3.2 Content-Level Private Extensions

Elements from the ATSC 3 namespace may be used within the OMA `PrivateExt` element, to indicate ATSC 3 content components related elements and attributes, as listed in Table 5.9.

Table 5.9 Content-Level Private Extensions

Name	Type	Category	Cardinality	Description	Data Type
Components	E2	NM/TM	0..1	Component sub-element. Contains the following elements: AudioComponent VideoComponent CCComponent AppComponent	
AudioComponent	E3	NM/TM	0..N	Role of the component. Textual description intended for human consumption regarding role of the component. Strings which could be used to describe role of component of ATSC3.0 service include: “Complete main” “Music” “Dialog” “Effects” “Visually impaired” “Hearing impaired” “Commentary” Any other useful description for a viewer can be provided. Contains the following attribute: language	String
Language	A	NM/TM	0..1	This element declares for the end users that this component is available in the language represented by the value of this element. The textual value of this element can be made available for the end users in different languages. In such a case the language used to represent the value of this element is	String

				signaled using the built-in XML attribute 'xml:lang'. See section 7 [7], Multi-language support.	
VideoComponent	E3	NM/ TM	0..N	<p>Role of the component.</p> <p>Textual description intended for human and/ or application consumption regarding role of the component.</p> <p>Strings which could be used to describe role of component of ATSC3.0 service include:</p> <p>“Alternative camera view”</p> <p>“Sign language inset”</p> <p>“Quarterback Helmet Cam”</p> <p>“3D video”</p> <p>Any other useful description for a viewer can be provided.</p> <p>Contains the following attribute:</p> <p>language</p>	String
Language	A	NM/TM	0..1	<p>This element declares for the end users that this component is available in the language represented by the value of this element.</p> <p>The textual value of this element can be made available for the end users in different languages. In such a case the language used to represent the value of this element is signaled using the built-in XML attribute 'xml:lang'. See section 7 [7], Multi-language support.</p>	String
CCComponent	E3	NM/ TM	0..N	<p>Role of the component.</p> <p>Textual description intended for human consumption regarding role of the component.</p> <p>Strings which could be used to describe role of component of ATSC3.0 service include:</p> <p>“Normal”</p> <p>“Easy reader”</p> <p>Any other useful description for a viewer can be provided.</p> <p>Contains the following attribute:</p> <p>language</p>	
Language	A	NM/TM	0..1	<p>This element declares for the end users that this component is available in the language represented by the value of this element.</p> <p>The textual value of this element can be made available for the end users in different languages. In such a case the language used to represent the value of this element is signaled using the built-in XML attribute 'xml:lang'. See section 7 [7] Multi-language support.</p>	String
AppComponent	E2	NM/ TM	0..N	<p>Role of the component.</p> <p>Textual description intended for human consumption regarding role of the component.</p> <p>Strings which could be used to describe role of component of ATSC3.0 service include:</p> <p>“On Demand”</p> <p>Any other useful description for a viewer can be provided.</p> <p>Contains the following attribute:</p> <p>language</p>	
Language	A	NM/TM	0..1	<p>This element declares for the end users that this component is available in the language</p>	String

				represented by the value of this element. The textual value of this element can be made available for the end users in different languages. In such a case the language used to represent the value of this element is signaled using the built-in XML attribute 'xml:lang'. See section 7 [7] Multi-language support.	
ContentIcon	E2	NM/TM	0..N	URL pointing to an icon (image) used to represent the content element in the ESG. Multiple URLs could be used to point to icons (images) of different width and height or different representation formats. Contains the following optional attributes: MIMETYPE width height dataSize	anyURI
MIMETYPE	A	NM/TM	0..1	The optional MIME type of the icon allowing receivers to preemptively ignore fetching image types they are not capable of using.	String
width	A	NM/TM	0..1	Width of the referenced image in pixels	unsignedInt
height	A	NM/TM	0..1	Height of the referenced image in pixels	unsignedInt
dataSize	A	NM/TM	0..1	Size of the image data in bytes.	unsignedInt
Preview	E2	NM/TM	0..N	The preview element provides a way to reference promotional content for a particular ESG content element. Examples include movie trailers, news promos and banner images. Multiple preview items can be included in a content element extension. It is expected that each item would provide different types of promotional material as described in the Description element. Contains the following elements: PreviewIcon Description PreviewContent Contains the following optional attribute: usage	
usage	A	NM/TM	0..1	The optional usage attribute describes how the preview item is intended to be used within the ESG. Preview items specifying usage values that are not known to the ESG implementation shall be ignored. The following values are defined: "promo" – The default value indicating that the preview is promotional and likely video content. "preface" – Indicates that the preview material is intended to be display during a channel change to the particular content element. See section 5.2.2.3.2.1. "banner" – Indicates that the preview element represents a banner ad and may be displayed in the appropriate area.	String
PreviewIcon	E3	NM/TM	0..N	URI pointing to an icon (image) used to represent the preview element in the ESG. Multiple URIs could be used to point to icons (images) of different width and height or different representation formats.	anyURI

				Contains the following optional attributes: MIMETYPE width height dataSize	
MIMETYPE	A	NM/TM	0..1	The optional MIME type of the icon allowing receivers to preemptively ignore fetching image types they are not capable of using.	String
width	A	NM/TM	0..1	Width of the referenced image in pixels	unsignedInt
height	A	NM/TM	0..1	Height of the referenced image in pixels	unsignedInt
dataSize	A	NM/TM	0..1	Size of the image data in bytes.	unsignedInt
Description	E3	NM/TM	1..N	Extended Description element which includes sub-elements to indicate description and phonetic information about description. Contains the following elements: SpeechInfoURI SpeechInfo Contains the following attributes: text xml:lang	
text	A	NM/TM	1	Description of the Preview	String
xml:lang	A	NM/TM	0..1	The language of the text attribute expressed with XML attribute 'xml:lang'	String
SpeechInfoURI	E4	NM/TM	0..N	The URI address where SpeechInfo object for parent Description element is acquired. Speech file may be encoded in SSML format (http://www.w3.org/TR/speech-synthesis11/) or similar types of mark-up languages. Contains the following attributes: content-type content-enc	anyURI
content-type	A	NM/TM	0..1	Content-type of SpeechInfo object referenced by SpeechInfoURI.	String
content-enc	A	NM/TM	0..1	Content encoding of SpeechInfo object referenced by SpeechInfoURI.	String
SpeechInfo	E4	NM/TM	0..N	Embedded Speech information object for parent Description element. Contains the following attributes: content-type content-enc	anyURI
content-type	A	NM/TM	0..1	Content-type of SpeechInfo object.	String
content-enc	A	NM/TM	0..1	Content encoding of SpeechInfo object.	String
PreviewContent	E3	NM/TM	0..N	URI pointing to content that can be displayed as preview data for the content element within the ESG. Multiple URIs could be used to reference content of different width and height or different representation formats. It is also possible to reference other types of data besides multimedia but it is expected that the URIs referenced here would reference similar semantic content with differing representations for example images of different encoding formats; i.e., png, jpg, or gif. Contains the following optional attributes: MIMETYPE width height dataSize	anyURI

MIMETYPE	A	NM/TM	0..1	The optional MIME type of the content specified by PreviewContent element allowing receivers to preemptively ignore fetching image types they are not capable of using.	String
width	A	NM/TM	0..1	Width of the referenced content specified by PreviewContent element in pixels	unsignedInt
height	A	NM/TM	0..1	Height of the referenced content specified by PreviewContent element in pixels	unsignedInt
dataSize	A	NM/TM	0..1	Size of the content specified by PreviewContent element data in bytes.	unsignedInt

Note: The attributes associated with the ContentIcon, PreviewIcon, and PreviewContent elements are optional. They can be provided as hints to allow the receiver ESG system to avoid accessing image and preview data that it cannot process.

5.2.2.3.2.1 Preview Usage Discussion

The preview element allows one or more previews to be associated with a content item. It is expected that, for ESG implementations that support promotional previews, when a content element is selected within the ESG, access to the previews would be provided in some way. It is further expected that the preview description and icon, if present, would allow the user to determine if they are interested in accessing the preview.

The usage attribute on each preview gives the ESG system a hint as to how the preview data is intended to be used. The default value, “promo”, would indicate that the preview contains audio and video content promoting the content item. Examples of these types of previews would be movie trailers, news promos, and other types of familiar promotional material.

The “preface” usage value indicates that the referenced preview data can be displayed during service changes. This would typically be an image slate or single frame that can be displayed when the user selects the particular content item for viewing—if the selection is going to take more than a receiver-defined time limit (e.g., 1-2 seconds).

The “banner” usage indicates that the preview material was created in an aspect ratio optimal for banner ads. In this case, the banner would simply be displayed when the user selected the content on the ESG. Note that a banner and various other preview items could be provided for the same content item within the ESG.

5.2.2.3.3 Device Capabilities

5.2.2.3.3.1 Device Capabilities Related Content-Level Private Extensions

Elements from the ATSC 3 namespace may be used within the OMA PrivateExt element, to indicate an ATSC 3.0 device capabilities related element, as given in Table 5.10. The sa:Capabilities XML element specifies the capabilities and capability groups¹ required in the receiver to be able to create a meaningful presentation of the content. Using this element, it is possible to express multiple alternate sets of required capabilities and capability groups, the support for any one of the multiple alternate sets is sufficient to create a meaningful presentation. This is done by using a logical or expression in the sa:Capabilities element. It is also possible to express decoder features to HTTP servers and A/344 [15] applications (see Table 5.11 Note 1)

¹ A capability group is a set of capabilities

using the syntax described in this section (see also A/331 Section 7.1.2.4 [2], A/344 Section 9.13 [15]).

The `sa:Features` XML element specifies capabilities and capability groups, whether essential or optional, usable to create meaningful presentations of this Content, if supported by a receiver. This element can be used to provide content properties in the Service Guide or to filter content in accordance with user preferences. The `sa:Features` element is a logical expression of the form specified in Section 5.2.2.3.3.2 and is not constrained to use capability codes designated therein as “Required”. When not already provided in disjunctive normal form² (DNF), this logical expression can be expanded into DNF, wherein each term indicates a set of capabilities usable in one or more meaningful presentations of this Content. A receiver can evaluate the entire `sa:Features` element to discern whether it can meaningfully present this Content, thereby duplicating the functionality of `sa:Capabilities`, but can analyze and evaluate each term of the DNF to discern whether any capabilities that are preferred or of interest are available for meaningful presentations of this Content.

Table 5.10 Device Capabilities Related Content-Level Private Extensions

Name	Type	Category	Cardinality	Description	Data Type
Content	E			'Content' fragment ...	
...					
PrivateExt	E1	NO/TO	0..1	An element serving as a container for proprietary or application-specific extensions.	
sa:Capabilities	E3	NO/TM	0..1	Capabilities and capability groups required for decoding and presenting the content signaled using capability codes, capability strings and Boolean operators (and/or). This string shall conform to the normative syntax defined for <code>capabilities</code> described in Section 5.2.2.3.3.2	string
sa:Features	E3	NO/TM	0..1	Capabilities and capability groups usable when decoding and presenting the content signaled using capability codes, capability strings and Boolean operators (and/or). This string shall conform to the normative syntax defined for <code>capabilities</code> described in Section 5.2.2.3.3.2.	string

5.2.2.3.3.2 Device Capabilities Syntax and Semantics

This section defines the syntax for the required device capabilities and capability groups indicated by `capabilities`. The syntax is described using the Augmented Backus-Naur Form (ABNF) grammar defined in RFC 5234 [5], and UTF-8 as defined in RFC 3629 [6] (Section 4). Rules are separated from definitions by an equal "=", indentation is used to continue a rule definition over more than one line, literals are quoted with "", parentheses "(" and ")" are used to group elements, optional elements are enclosed in "[" and "]" brackets, and elements may be preceded with `<n>*` to designate n or more repetitions of the following element; n defaults to 0.

Syntax of `capabilities` shall be as specified below:

² DNF is a canonical normal form of a logical formula consisting of a disjunction of conjunctions, wherein each conjunction is a “term”. Compared to an expression in DNF, an equivalent expression that is not in DNF can be more compact.

```

ccode                = 1*4HEXDIG
capability_string_code = ubyte "=" 1*utf8
ubyte                = 1*3DIGIT
utf8                  = *( UTF8-char )

boperator            = and / or
and                  = "&"
or                   = "|"
expr                 = ccode
                      / capability_string_code
                      / expr WSP expr WSP boperator

capabilities         = expr

```

The semantics of `capabilities` shall be as specified below.

`ccode` – This terminal symbol represents a certain capability or capability group. This symbol evaluates as “true” if and only if the device has the capability or capability group identified. Values of `ccode` shall be a code point from Table 5.11.

`capability_string_code` – The first operand `ubyte` represents the capability category code. Values of `ubyte` shall be from Table 5.12 `capability_category_code` column. The second operand specifies the value of the capability. This symbol evaluates as “true” if and only if the device has the capability identified. Characters chosen from UTF8-char shall not include Whitespace (WSP).

`boperator` – This nonterminal symbol represents a Boolean operator.

`and` – This nonterminal symbol represents the logical-and symbol.

`or` – This nonterminal symbol represents the logical-or symbol.

`expr` – This recursive nonterminal symbol represents a sequence of `ccode` symbols, `capability_string_code` symbols, and postfix logical operations. In an `expr`, when the `boperator` is “and”, this symbol evaluates as “true” if and only if both the first and second operands evaluate as “true”; and when the `boperator` is “or”, this symbol evaluates as “true” if and only if one or both of the first and second operands evaluate as “true.”

`capabilities` – This nonterminal represents capabilities and capability groups required for decoding and presenting the content signaled. If this nonterminal evaluates as “true”, capabilities and capability groups required to be able to create a meaningful presentation of the content are present. Using this nonterminal it is possible to express multiple alternate sets of capabilities and capability groups, the support for any one set of which is sufficient to create a meaningful presentation.

Table 5.11 Capability Codes

capability_code Meaning		Reference	Required (See Note 1)	Supported (See Note 2)
0x0000	Forbidden		n/a	n/a
Capability Category: Download Protocols				
0x0100-0x01FF	Reserved for future ATSC use.			
Capability Category: FEC Algorithms				
0x0200	AL FEC Repair-only	Section 5.3.8	X	X
0x0201	STAGGERCAST	A/331 Sections 7.1.5.1 and 7.2.3.3 [2]		X

capability_code	Meaning	Reference	Required (See Note 1)	Supported (See Note 2)
0x0201-0x02FF	Reserved for future ATSC use.			
Capability Category: Wrapper/Archive Formats				
0x0300-0x03FF	Reserved for future ATSC use.			
Capability Category: Compression Algorithms				
0x0400-0x04FF	Reserved for future ATSC use.			
Capability Category: Media Types (RMP – See Note 3)				
0x0500	[Reserved for AVC standard definition video]	Section 5.3.1		
0x0501	[Reserved for AVC high definition video]	Section 5.3.1		
0x0502	AC-3 audio	A/103 Section A.2.10 [12]		
0x0503	E-AC-3 audio	A/103 Section A.2.11 [12]		
0x0504	DTS-HD audio	A/103 Section A.2.18 [12]		
0x0505	HE AAC v2 with MPEG Surround	A/103 Section A.2.21 [12]		
0x0506	HE AAC v2 Level 6 audio	A/103 Section A.2.22 [12]		
0x0507	Frame-compatible 3D video (Side-by-Side)	A/103 Section A.2.23 [12]		
0x0508	Frame-compatible 3D video (Top-and-Bottom)	A/103 Section A.2.24 [12]		
0x0509	ATSC 3.0 HEVC Video	Section 5.3.3	X	X
0x050A	ATSC 3.0 HDR Video	Section 5.3.4	X	X
0x050B	Dolby® AC4 Audio	A/342 Part 2 [10]	X	X
0x050C	MPEG-H Audio	A/342 Part 3 [11]	X	X
0x050D	IMSC1 Text Profile	A/343 [13]	X	X
0x050E	IMSC1 Image Profile	A/343 [13]	X	X
0x050F	4K Resolution	A/341 [9]		X
0x0510	ATSC 3.0 HDR with ST 2094-10	Section 5.3.6		X
0x0511	ATSC 3.0 SDR with SL-HDR1 SEI	Section 5.3.7		X
0x0512	ATSC 3.0 SHVC Video	Section 5.3.9		X
0x0513	HFR with one temporal sub-layer	Section 5.3.10		X
0x0514	HFR with unfiltered temporal sub-layers	Section 5.3.11		X
0x0515	HFR with filtered temporal sub-layers	Section 5.3.12		X
0x0516	ATSC 3.0 Fixed/Mobile 3D HEVC	Section 5.3.13		X
0x0517	ATSC 3.0 Fixed/Mobile 3D SHVC	Section 5.3.14		X
0x0518	ATSC 3.0 Wide Color Gamut	Section 5.3.15		X
0x0519	ATSC 3.0 HD Progressive Video	Section 5.3.16		X
0x051A	ATSC 3.0 Personalization Selection	Section 5.3.17		X
0x051B	ATSC 3.0 Dialog Enhancement	Section 5.3.18		X
0x051C	ATSC 3.0 Video Descriptive Services	Section 5.3.19		X
0x051D	ATSC 3.0 SD Progressive Video	Section 5.3.20		X
0x051E	ATSC 3.0 Legacy SD Video	A/341 Section 6.2.1 [9]		X
0x051F	ATSC 3.0 Interlaced HD Video	A/341 Section 6.2.2 [9]		X
0x0520-0x057F	Reserved for future ATSC use.			
Capability Category: Media Types (AMP – See Note 4)				

capability_code	Meaning	Reference	Required (See Note 1)	Supported (See Note 2)
0x0580	[Reserved for AVC standard definition video]	Section 5.3.1		
0x0581	[Reserved for AVC high definition video]	Section 5.3.1		
0x0582	AC-3 audio	A/103 Section A.2.10 [12]		
0x0583	E-AC-3 audio	A/103 Section A.2.11 [12]		
0x0584	DTS-HD audio	A/103 Section A.2.18 [12]		
0x0585	HE AAC v2 with MPEG Surround	A/103 Section A.2.21 [12]		
0x0586	HE AAC v2 Level 6 audio	A/103 Section A.2.22 [12]		
0x0587	Frame-compatible 3D video (Side-by-Side)	A/103 Section A.2.23 [12]		
0x0588	Frame-compatible 3D video (Top-and-Bottom)	A/103 Section A.2.24 [12]		
0x0589	ATSC 3.0 HEVC Video	Section 5.3.3	X	X
0x058A	ATSC 3.0 HDR Video	Section 5.3.4	X	X
0x058B	Dolby® AC4 Audio	A/342 Part 2[10]	X	X
0x058C	MPEG-H Audio	A/342 Part 3 [10]	X	X
0x058D	IMSC1 Text Profile	A/343 [13]	X	X
0x058E	IMSC1 Image Profile	A/343 [13]	X	X
0x058F	4K Resolution	A/341 [9]		X
0x0590	ATSC 3.0 HDR with ST 2094-10	Section 5.3.6		X
0x0591	ATSC 3.0 SDR with SL-HDR1 SEI	Section 5.3.7		X
0x0592	ATSC 3.0 SHVC Video	Section 5.3.9		X
0x0593	HFR with one temporal sub-layer	Section 5.3.10		X
0x0594	HFR with unfiltered temporal sub-layers	Section 5.3.11		X
0x0595	HFR with filtered temporal sub-layers	Section 5.3.12		X
0x0596	ATSC 3.0 Fixed/Mobile 3D HEVC	Section 5.3.13		X
0x0597	ATSC 3.0 Fixed/Mobile 3D SHVC	Section 5.3.14		X
0x0598	ATSC 3.0 Wide Color Gamut	Section 5.3.15		X
0x0599	ATSC 3.0 HD Progressive Video	Section 5.3.16		X
0x059A	ATSC 3.0 Personalization Selection	Section 5.3.17		X
0x059B	ATSC 3.0 Dialog Enhancement	Section 5.3.18		X
0x059C	ATSC 3.0 Video Descriptive Services	Section 5.3.19		X
0x059D	ATSC 3.0 SD Progressive Video	Section 5.3.20		X
0x059E	ATSC 3.0 Legacy SD Video	A/341 Section 6.2.1 [9]		X
0x059F	ATSC 3.0 Interlaced HD Video	A/341 Section 6.2.2 [9]		X
0x05A0-0x05FF	Reserved for future ATSC use.			
Capability Category: Internet Link				
0x0600	Internet link, downward rate 56,000 bps or better	A/103 Section A.2.25 [12]		
0x0601	Internet link, downward rate 512,000 bps or better	A/103 Section A.2.26 [12]		
0x0602	Internet link, downward rate 2,000,000 bps or better	A/103 Section A.2.27 [12]		

capability_code Meaning		Reference	Required (See Note 1)	Supported (See Note 2)
0x0603	Internet link, downward rate 10,000,000 bps or better	A/103 Section A.2.28 [12]		
0x0604-0x06FF	Reserved for future ATSC use.			
Capability Category: Interactive				
0x0700	Interactive Content Environment	A/344 [15] (all)	X	X
0x0701	<i>WSPath/atscVid</i>	A/344 [15] 8.2.1	X	X
0x0702	<i>WSPath/atscAud</i>	A/344 [15] 8.2.1	X	X
0x0703	<i>WSPath/atscCap</i>	A/344 [15] 8.2.1	X	X
0x0704	<i>WSPath/atscCD</i>	A/344 [15] 8.2.1	X	X
0x0705-0x07FF	Reserved for future ATSC use.			
Capability Category: Other				
0x0800	DRM	Section 5.3.21.1	X	X
0x0801	Companion Device	Section 5.3.21.2	X	X
0x0802-0x08FF	Reserved for future ATSC use.			
ATSC Reserved				
0x001-0x00FF, 0x0900- 0xFFFF	Reserved for future ATSC use.			
<p>Note 1 - Codes marked with an “X” in this column are those codes that have use when signaling “capabilities and capability groups required in the receiver to be able to create a meaningful presentation of the content” (as described in Section 5.2.2.3.3.1 above).</p> <p>Note 2 - Codes marked with an “X” in this column are those codes that have use when signaling the capabilities of receivers to HTTP servers (A/331 [2] Section 7.1.2.4) and A/344 Applications (A/344 [15] Section 9.13).</p> <p>Note 3 – Required or supported without using an interactive environment; e.g., the real RMP only.</p> <p>Note 4 – Required or supported using the interactive environment; e.g., the real RMP, HTML5 media stack, etc.</p>				

Table 5.12 Capability Categories and References

capability_category_code	Capability Category	Reference
0x00	Minimum HTTP Cache Size	Section 5.3.22.1
0x01	Minimum Broadcast Cache Size	Section 5.3.23
0x02-0xFF	Reserved for future ATSC use.	

5.3 Description of Code Points

The terms “RMP” and “AMP” as used in Table 5.11 and this section are not as commonly used in A/344 [15]. These refer to two separate environments within the receiver. The RMP is the native receiver environment. It is expected to support at least the essential capabilities to create useful presentations. The AMP is in the interactive environment intended to support broadcaster applications. As such, it can include additional functionality, which include support for a different set of capabilities. These different environments and their capabilities are separated into two similar sets of capability codes in the table above to cover the use cases where decoder capabilities exist in only one of the environments.

Other Code Points in Table 5.11 shall follow the description specified in the section referred in the column “Reference”.

Note: User private data, including capability codes, can be added with user-defined-namespace elements or attributes.

5.3.1 Capability Codes 0x0500, 0x0501, 0x580, 0x581: AVC Video

The capability codes 0x0500, 0x0501, 0x0580, and 0x0581 are allocated to represent AVC standard definition video and AVC high definition video, respectively. These codes should not be used but might be usable if a future version of the ATSC 3.0 standard defines full specifications for the use of AVC.

5.3.2 Capability Codes 0x0507, 0x0508, 0x0587, and 0x0588: 3D Video

The capability codes 0x0507, 0x0508, 0x0587, and 0x0588 are allocated to represent various 3D video configurations. These codes should not be used but might be usable if a future version of the ATSC 3.0 standard defines full specifications for their use.

5.3.3 Capability Codes 0x0509 and 0x0589: ATSC 3.0 HEVC Video

The `capability_code` values 0x0509 and 0x0589 shall represent the receiver ability (using the RMP or AMP, respectively) to decode and display or output video (including at least the base layer of HEVC scalable video) encoded using HEVC in conformance with the ATSC specification A/341 [9] but not requiring ability to support the constraints related to HDR in A/341 [9].

5.3.4 Capability Codes 0x050A and 0x058A: ATSC 3.0 HDR Video

The `capability_code` values 0x050A and 0x058A shall represent the receiver ability (using the RMP or AMP, respectively) to decode and display or output video encoded using HEVC in conformance with the ATSC specification A/341 [9] including the aspects of A/341 describing HDR. That is, the receiver's ability to decode and display or output HEVC video encoded in conformance with all constraints including constraints regarding HDR in A/341 [9].

5.3.5 Capability Codes 0x050F and 0x058F: 4K Resolution

The `capability_code` values 0x050F and/or 0x058F shall represent the receiver ability (using RMP or AMP respectively) to decode and display or output video with spatial resolution greater than or equal to 3840×2160 (nominal), which is encoded per A/341 [9] with spatial resolution greater than or equal to 3840×2160. Note that this represents the ability to display or output at 3840×2160, not merely the ability to decode video encoded at 3840×2160 and create a meaningful output.

5.3.6 Capability Codes 0x0510 and 0x0590: ATSC 3.0 HDR Video with ST2094-10 SEI

The `capability_code` values 0x0510 and/or 0x0590 shall represent the receiver (using the RMP or AMP respectively) ability to decode HEVC video encoded in conformance with the ATSC specification A/341 [9] and specifically to utilize ST 2094-10 metadata. Note that this represents the ability to utilize the ST 2094-10 metadata in the decoding process, as described by the ST 2094-10 SEI messages as codified in A/341 Section 6.3.2.2.1 [9].

5.3.7 Capability Codes 0x0511 and 0x0591: ATSC 3.0 SDR Video with SL-HDR1 SEI

The `capability_code` values 0x0511 and/or 0x0591 shall represent the receiver (using the RMP or AMP respectively) ability to decode HEVC video encoded in conformance with the ATSC specification A/341 [9] and specifically to utilize SL-HDR1 metadata. Note that this represents the ability to utilize SL-HDR1 metadata carried in the SL-HDR Information SEI messages as codified in A/341 Sections 6.3.2.1.1 and 6.3.2.1.2 [9].

5.3.8 Capability Code 0x0200: AL-FEC

The `capability_code` value 0x0200 shall represent the receiver ability to utilize AL-FEC data to perform error correction in conformance to the ATSC specification A/331 [2].

5.3.9 Capability Codes 0x0512 and 0x0592: ATSC 3.0 SHVC Video

The `capability_code` values 0x0512 and 0x0592 shall represent the receiver ability, in the RMP or AMP respectively, to decode and display or output video enhanced by an SHVC enhancement layer in conformance with the ATSC specification A/341 Sections 6.3.1, 6.3.2.1, 6.3.3.3, and 6.3.4 [9] as applied to the context determined by the other conjoined capability codes.

5.3.10 Capability Codes 0x0513 and 0x0593: HFR with One Temporal Sub-Layer

The `capability_code` values 0x0513 and/or 0x0593 shall represent the receiver ability (using RMP or AMP, respectively) to decode and display or output high frame rate (i.e., a picture rate of 100, 120/1.001, 120) video encoded using HEVC with exactly one temporal sub-layer in conformance with the ATSC specification A/341 Section 6.3.4 [9]. A code from this section shall not appear in a conjunction with any code from Section 5.3.11 or Section 5.3.12.

5.3.11 Capability Codes 0x0514 and 0x0594: HFR with Unfiltered Temporal Sub-Layers

The `capability_code` values 0x0514 and 0x0594 shall represent the receiver ability, in the RMP or AMP respectively, to decode and display or output high frame rate (i.e., a picture rate of 100, 120/1.001, 120) video using HEVC encoded with exactly two temporal sub-layers in conformance with the ATSC specification A/341 Section 6.3.4 [9] without the temporal filtering described in A/341 Section 6.3.4.1 [9]. A code from this section shall not appear in a conjunction with any code from Section 5.3.10 or Section 5.3.12.

5.3.12 Capability Codes 0x0515 and 0x0595: HFR, Temporal Filtering

The `capability_code` values 0x0515 and 0x0595 shall represent the receiver ability, in the RMP or AMP respectively, to decode and display or output high frame rate (i.e., a picture rate of 100, 120/1.001, 120) video using HEVC encoded with exactly two temporal sub-layers and in conformance with the ATSC specification A/341 Section 6.3.4 [9] and with temporal filtering in conformance with A/341 Section 6.3.4.1 [9]. A code from this section shall not appear in a conjunction with any code from Section 5.3.10 or Section 5.3.11.

5.3.13 Capability Codes 0x0516 and 0x0596: ATSC 3.0 Fixed/Mobile 3D HEVC

The `capability_code` values 0x0516 and 0x0596 shall represent the receiver ability, in the RMP or AMP respectively, to decode and display or output stereoscopic video using HEVC with independently encoded left and right views, subject to the constraints of ATSC specification A/341 Sections 6.2.3 and 6.3.3 [9] as described in Annex C [9].

5.3.14 Capability Codes 0x0517 and 0x0597: ATSC 3.0 Fixed/Mobile 3D SHVC

The `capability_code` values 0x0517 and 0x0597 shall represent the receiver ability, in the RMP or AMP respectively, to decode and display or output stereoscopic video using HEVC having left and right views further encoded using SHVC, subject to the constraints of ATSC specification A/341 Sections 6.2.3, 6.3.1, and 6.3.3 [9] as described in Annex C [13].

5.3.15 Capability Codes 0x0518 and 0x0598: ATSC 3.0 Wide Color Gamut

The `capability_code` values 0x0518 and 0x0598 shall represent the receiver ability, in the RMP or AMP respectively, to decode and display or output video having colors outside the ITU-R BT.709 [16] gamut when encoded using HEVC with primaries and matrix coefficients (i.e., system colorimetry) of ITU-R BT.2020 [17] and ITU-R BT.2100 [18], subject to the constraints of ATSC specification A/341 Section 6.3.2. [9]

5.3.16 Capability Codes 0x0519 and 0x0599: ATSC 3.0 HD Progressive Video

The `capability_code` values 0x0519 and 0x0599 shall represent the receiver ability, in the RMP or AMP respectively, to decode and display or output progressive video formats between 720 and 1440 lines, as constrained in Section 6.2.3 of ATSC specification A/341 [9] in the context of the other conjoined capability codes.

5.3.17 Capability Codes 0x051A and 0x059A: Personalization Selection

The `capability_code` values 0x051A and 0x059A shall represent the receiver ability, in the RMP or AMP respectively, to decode and reproduce or output audio subject to a personalization selection by the user, as specified in ATSC specification A/342 Part 1 [19], in the context of the other conjoined capability codes.

5.3.18 Capability Codes 0x051B and 0x059B: Dialog Enhancement

The `capability_code` values 0x051B and 0x059B, shall represent the receiver ability, in the RMP or AMP respectively, to decode and reproduce or output audio subject to a personalization control by the user to set a relative level of dialog, as specified in ATSC specification A/342 Part 1 [19], in the context of the other conjoined capability codes.

5.3.19 Capability Codes 0x051C and 0x059C: Video Descriptive Service

The `capability_code` values 0x051C and 0x059C shall represent the receiver ability, in the RMP or AMP respectively, to decode and reproduce or output video descriptive services subject to a personalization control by a user, as specified in ATSC specification A/342 Part 1 [19], in the context of the other conjoined capability codes.

5.3.20 Capability Codes 0x051D and 0x059D: ATSC 3.0 SD Progressive Video

The `capability_code` values 0x051D and 0x059D shall represent the receiver ability, in the RMP or AMP respectively, to decode and display or output progressive video formats having fewer than 720 lines, as constrained in Section 6.2.3. of ATSC specification A/341 [9] in the context of the other conjoined capability codes.

5.3.21 Capability Category "Other" (0x08xx)

5.3.21.1 Capability Code 0x0800: DRM

The `capability_code` value 0x0800 shall represent that the Receiver supports Digital Rights Management, or that the service is encrypted and requires one. Note that this does not indicate a specific DRM system.

5.3.21.2 Capability Code 0x0801: Companion Device

The `capability_code` value 0x0801 shall represent that the Receiver supports a Companion Device as defined in A/338 [14], or that the service requires one.

5.3.22 Capability Category String Codes (ubyte)

This section identifies string “token” codes that can be used with the `capability_string_code` ubyte value and defines the syntax of the “value” (utf8) of that token.

5.3.22.1 ubyte 0x00: Minimum HTTP Cache Size

The ubyte value 0x00 shall represent that the service or content requires, or the Receiver has, an HTTP cache size in bytes of at least the value of the token, utf8. The syntax of utf8 shall be a decimal integer that represents a minimum cache size in multiples of 100,000 bytes; e.g., “00=5” signals that 500,000 bytes in HTTP cache is needed or supported. This cache is available for any Broadcaster Application signaled in the HELD. See A/331 [2]. The cache content includes HTTP content requested by the Broadcaster Application while executing. Broadcast content is not included in this number. See Section 5.3.10.2.

5.3.23 ubyte 0x01: Minimum Broadcast Cache Size

The ubyte value 0x01 shall represent that the service or content requires, or the Receiver has, a broadcast cache size in bytes of at least the value of the token, utf8. The syntax of utf8 shall be a decimal integer that represents a minimum cache size in multiples of 100,000 bytes; e.g., “01=2” signals that 200,000 bytes in broadcast is needed or supported. This cache is available for any Broadcaster Application signaled in the HELD. See A/331 [2]. All other cache content associated with non-executing `appContextId`'s can be flushed by the Receiver as needed to make up the signaled amount available to the currently executing Broadcaster Application. The cache content includes: the HELD `HTMLEntryPackage`, NRT content with the same `appContextId`, and storage of Broadcaster Application originated data.

5.4 SG Data Encapsulation

The Service Guide fragments specified in Section 5.3 of the present document shall be encapsulated in Service Guide Delivery Units (SGDUs), and the SGDUs shall be described in Service Guide Delivery Descriptors (SGDDs), as specified in Section 5.4.1 of the OMA BCAST SG specification [7]. The Service Guide Delivery Unit (SGDU) structure is the transport container for ATSC 3.0 service guide fragments. Broadcast Systems and the Reference Receiver shall support the Service Guide Delivery Unit structure as specified by Section 5.4.1.3 of the OMA BCAST 1.0.1 Service Guide [7], with the following constraints:

- The value of `extension_offset` field of the `unitHeader` structure shall be equal to zero in SGDUs conforming to this version of this specification. The Reference Receiver shall be able to process an SGDU with a non-zero value for `extension_offset` (e.g., by ignoring the `extensions` field).
- The `fragmentEncoding[i]` field shall not take value of 1 or 2 or 3 for any value of `i` in the range 0 to `n_o_service_guide_fragments` in a SGDU. There shall be at least one value of `i` in the range 0 to `n_o_service_guide_fragments` for which value of `fragmentEncoding[i]` shall be equal to 0 in each SGDU conforming to this version of this specification. The reference receiver shall ignore fragment data associated with a non-zero `fragmentEncoding[i]` value for any value of `i` in the range 0 to `n_o_service_guide_fragments`.
- For any value of `i` in the range 0 to `n_o_service_guide_fragments`, when value of `fragmentEncoding[i]` is equal to 0, the `fragmentType` field shall not take value of 4, 5, 6, 7, 8, 9 for a SGDU. There shall be at least one value of `i` in the range 0 to `n_o_service_guide_fragments` for which `fragmentType` value shall be equal to 0 or 1 or 2 or 3

and `fragmentEncoding[i]` value shall be equal to 0 in each SGDU conforming to this version of this specification. The reference receiver shall ignore data in `XMLFragment` field with associated `fragmentType` field with value equal to 0 or greater than 3 for any value of `i` in the range 0 to `n_o_service_guide_fragments` when `fragmentEncoding[i]` is equal to 0.

5.5 SG Delivery

5.5.1 SG delivery over Broadcast

When SG data are delivered via broadcast, the SGDUs and SGDDs shall be delivered as specified in Section 5.4.2 of the OMA BCAST SG specification [7], except that a single LCT component of a ROUTE [2] session (called the Service Guide Announcement Channel) shall be used for delivery of the SGDDs. SGDUs are referenced from within SGDDs by means of the **ServiceGuideDeliveryDescriptor.DescriptorEntry.Transport** element. If AL-FEC coding is not employed, SGDUs shall be transported using the modified Compact No-Code FEC scheme defined in A/331 [3] where the FEC Payload ID is formatted as a 32-bit `start_offset`. If AL-FEC coding is employed, SGDUs shall be transported using RFC 6330 [20]. EFDTs shall be transmitted in the transport session delivering the Service Guide fragments.

5.5.2 SG delivery over Broadband

When SG data are delivered via broadband, the delivery shall conform to the specifications of section 5.4.3 of the OMA BCAST SG specification [7].

5.6 SG Data Update and Management

Update and management of the SG data shall conform to the specifications of Section 5.5 of the OMA BCAST SG specification [7].

Annex A Schema

This Annex contains the normative XML Schema for elements and attributes defined in this specification.

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:sa="tag:atsc.org,2016:XMLSchemas/ATSC3/SA/1.0/"
xmlns:rrt="tag:atsc.org,2016:XMLSchemas/ATSC3/RRT/1.0/"
  targetNamespace="tag:atsc.org,2016:XMLSchemas/ATSC3/SA/1.0/"
  elementFormDefault="qualified">
  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="w3C/xml.xsd"/>
  <xs:import namespace="tag:atsc.org,2016:XMLSchemas/ATSC3/RRT/1.0/"
    schemaLocation="RRT-1.0-20210128.xsd"/>
  <xs:annotation>
    <xs:documentation>
      The definition of this schema can also be found in an XML schema file, SA-1.0-20210312.xsd at the ATSC
      website.The XML schema file RRT-1.0-20210128.xsd can also be found at the ATSC website.
    </xs:documentation>
  </xs:annotation>
  <xs:element name="Capabilities" type="sa:CapabilitiesType" />
  <xs:element name="Features" type="sa:CapabilitiesType" />
  <xs:simpleType name="CapabilitiesType"><xs:restriction base="xs:string"/></xs:simpleType>
</xs:annotation>
  <xs:documentation>
    Name and Description elements in Service and Content Fragments of OMA BCAS service guide will be replaced
    with following extended elements
  </xs:documentation>
</xs:annotation>

<xs:element name="Name" type="sa:NameDescriptionType" />
<xs:element name="Description" type="sa:NameDescriptionType" />

<xs:complexType name="NameDescriptionType">
  <xs:sequence>
    <xs:element name="SpeechInFOUR" minOccurs="0" maxOccurs="unbounded">
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension base="xs:anyURI">
            <xs:attribute name="content-type" type="xs:string" use="optional"/>
            <xs:attribute name="content-enc" type="xs:string" use="optional"/>
            <xs:anyAttribute processContents="skip"/>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
```

```

        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
    <xs:element name="SpeechInfo" minOccurs="0" maxOccurs="unbounded">
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension base="xs:string">
            <xs:attribute name="content-type" type="xs:string" use="optional"/>
            <xs:attribute name="content-enc" type="xs:string" use="optional"/>
            <xs:anyAttribute processContents="skip"/>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
    <xs:any namespace="##other" processContents="skip" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="text" type="xs:string" use="required" />
  <xs:attribute ref="xml:lang" use="optional"/>
  <xs:anyAttribute processContents="skip"/>
</xs:complexType>

<xs:element name="ContentAdvisoryRatings" type="sa:CARatingType"/>
<xs:complexType name="CARatingType">
  <xs:sequence>
    <xs:element name="RegionIdentifier" type="xs:unsignedByte"
      minOccurs="0" maxOccurs="1"/>
    <xs:element name="RatingDescription" maxOccurs="1">
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension base="xs:string">
            <xs:attribute ref="xml:lang" use="optional"
              default="en"/>
            <xs:anyAttribute processContents="skip"/>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
    <xs:element name="RatedDimensions" type="xs:unsignedByte"
      minOccurs="0" maxOccurs="1"/>
    <xs:element name="RatingDimVal" type="sa:RatingDimValType"
      minOccurs="1" maxOccurs="unbounded"/>
    <xs:any namespace="##other" processContents="skip" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:anyAttribute processContents="skip"/>
</xs:complexType>
<xs:complexType name="RatingDimValType">
  <xs:sequence>
    <xs:element name="RatingDimension" type="xs:unsignedByte"
      minOccurs="0" maxOccurs="1"/>

```

```

        <xs:element name="RatingValueString" type="xs:string"
            minOccurs="1"/>
        <xs:any namespace="##other" processContents="skip" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
    <xs:anyAttribute processContents="skip"/>
</xs:complexType>

<xs:element name="OtherRatings" type="sa:OtherRatingType"/>
    <xs:complexType name="OtherRatingType">
        <xs:sequence>
            <xs:choice>
                <xs:element name="RatingInformationString" type="xs:string" minOccurs="1"/>
                <xs:element name="RatingInformationData" type="sa:RatingContainerType" minOccurs="1"/>
            </xs:choice>
            <xs:any namespace="##other" processContents="skip" minOccurs="0" maxOccurs="unbounded"/>
        </xs:sequence>
        <xs:attribute name="ratingScheme" type="xs:anyURI" use="required" />
        <xs:anyAttribute processContents="skip"/>
    </xs:complexType>
<xs:complexType name="RatingContainerType">
    <xs:sequence>
        <xs:any namespace="##other" processContents="lax" minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
    <xs:anyAttribute processContents="skip"/>
</xs:complexType>

<xs:element name="ATSC3ServiceExtension" type="sa:ATSC3ServiceExtensionType" >
    <xs:annotation>
        <xs:documentation>
This element is a wrapper for ATSC service extensions to OMA BCAS T SG Service fragments. It shall only be
used inside a PrivateExt element within a Service fragment.
        </xs:documentation>
    </xs:annotation>
</xs:element>

<xs:complexType name="ATSC3ServiceExtensionType">
    <xs:sequence>
        <xs:element name="Icon" minOccurs="0" maxOccurs="unbounded">
            <xs:complexType>
                <xs:simpleContent>
                    <xs:extension base="xs:anyURI">
                        <xs:attribute name="MIMETYPE" type="xs:string" use="optional" />
                        <xs:attribute name="width" type="xs:unsignedInt" use="optional" />
                        <xs:attribute name="height" type="xs:unsignedInt" use="optional" />
                        <xs:attribute name="dataSize" type="xs:unsignedInt" use="optional" />
                        <xs:anyAttribute processContents="skip"/>
                    </xs:extension>
                </xs:simpleContent>
            </xs:complexType>
        </xs:element>
    </xs:sequence>

```

```

</xs:element>
<xs:element name="MajorChannelNum" type="sa:LangString" minOccurs="0" maxOccurs="1"/>
<xs:element name="MinorChannelNum" type="sa:LangString" minOccurs="0" maxOccurs="1"/>
<xs:element name="RatingRegionTables" type="rrt:RRSType" minOccurs="0" maxOccurs="1"/>
<xs:any namespace="##other" processContents="skip" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>

<xs:element name="Components" type="sa:ComponentsType" >
  <xs:annotation>
    <xs:documentation>
      This element is a wrapper for ATSC media extensions to OMA BCASST SG Content fragments. It shall only be used
      inside a PrivateExt element within a Content fragment.
    </xs:documentation>
  </xs:annotation>
</xs:element>

<xs:complexType name="ComponentsType">
  <xs:sequence>
    <xs:element name="VideoComponent" type="sa:IndividualComponentType" minOccurs="0"
      maxOccurs="unbounded"/>
    <xs:element name="AudioComponent" type="sa:IndividualComponentType" minOccurs="0"
      maxOccurs="unbounded"/>
    <xs:element name="CCComponent" type="sa:IndividualComponentType" minOccurs="0"
      maxOccurs="unbounded"/>
    <xs:element name="AppComponent" type="sa:IndividualComponentType" minOccurs="0"
      maxOccurs="unbounded"/>
    <xs:any namespace="##other" processContents="skip" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:anyAttribute processContents="skip"/>
</xs:complexType>

<xs:complexType name="IndividualComponentType">
  <xs:complexContent>
    <xs:extension base="sa:LangString">
      <xs:attribute name="language" type="xs:string" use="optional" default="en"/>
      <xs:anyAttribute processContents="skip"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="LangString">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute ref="xml:lang" use="optional" default="en"/>
      <xs:anyAttribute processContents="skip"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>

<xs:element name="ContentIcon" >
<xs:annotation><xs:documentation>This element is only used inside a PrivateExt element within a Content

```


fragment as defined in Table 5.7 and its cardinality is defined in Table 5.9.

```

</xs:documentation></xs:annotation>
  <xs:complexType>
    <xs:simpleContent>
      <xs:extension base="xs:anyURI">
        <xs:attribute name="MIMETYPE" type="xs:string" use="optional" />
        <xs:attribute name="width" type="xs:unsignedInt" use="optional" />
        <xs:attribute name="height" type="xs:unsignedInt" use="optional" />
        <xs:attribute name="dataSize" type="xs:unsignedInt" use="optional" />
        <xs:anyAttribute processContents="skip"/>
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
</xs:element>

<xs:element name="Preview" type="sa:PreviewType" />
  <xs:complexType name="PreviewType">
    <xs:sequence>
      <xs:element name="PreviewIcon" minOccurs="0" maxOccurs="unbounded">
        <xs:complexType>
          <xs:simpleContent>
            <xs:extension base="xs:anyURI">
              <xs:attribute name="MIMETYPE" type="xs:string" use="optional" />
              <xs:attribute name="width" type="xs:unsignedInt" use="optional" />
              <xs:attribute name="height" type="xs:unsignedInt" use="optional" />
              <xs:attribute name="dataSize" type="xs:unsignedInt" use="optional" />
              <xs:anyAttribute processContents="skip"/>
            </xs:extension>
          </xs:simpleContent>
        </xs:complexType>
      </xs:element>
      <xs:element name="Description" type="sa:NameDescriptionType" minOccurs="1"
maxOccurs="unbounded"/>
      <xs:element name="PreviewContent" minOccurs="0" maxOccurs="unbounded">
        <xs:complexType>
          <xs:simpleContent>
            <xs:extension base="xs:anyURI">
              <xs:attribute name="MIMETYPE" type="xs:string" use="optional" />
              <xs:attribute name="width" type="xs:unsignedInt" use="optional" />
              <xs:attribute name="height" type="xs:unsignedInt" use="optional" />
              <xs:attribute name="dataSize" type="xs:unsignedInt" use="optional" />
              <xs:anyAttribute processContents="skip"/>
            </xs:extension>
          </xs:simpleContent>
        </xs:complexType>
      </xs:element>
      <xs:any namespace="##other" processContents="skip" minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
    <xs:attribute name="usage" type="xs:string" use="optional" default="promo"/>
  </xs:complexType>

```

```
<xs:anyAttribute processContents="skip"/>  
</xs:complexType>  
</xs:schema>
```

– End of Document –